


OptiTap® Cables



OptiTap® compatible outdoor rated fiber optic cables for FTTx applications

NetSource OptiTap® cable assembly solutions provide the speed and flexibility your network requires in any environment. The ease of our plug and play, pre-terminated cable assemblies saves time and money in the field. With a variety of cable and connector options NetSource OptiTap® cable assemblies can address all of your outside plant network needs.

Our OptiTap® solutions are designed for the most challenging environments, and perform under diverse conditions, extreme temperatures, in areas of high moisture or excessive dryness, and heavy RF interference.



260 Progress Drive
Manchester, CT 06042

P-800-557-8818
F-860-649-6002
info@netsource-inc.com

*Our Commitment to Quality and
Customer Service is Our Connection to You*

OptiTap® Cable Specifications

OptiTap® Cable Assembly Solutions

OptiTap® connector technology is the industry standard in FTTx installations offering a variety of configurations depending on your To-The-House project specifications. They are designed for rapid connection to external flush mounted bulkhead adapters on terminals or closures and can be pulled through loose tube / tight buffered 1.25 inch conduits.

Cables Available

- Flat Drop Dielectric
 - Flat Drop Toneable
 - Round Armor 5.5MM
 - Round Indoor Outdoor 4.8MM
- ** peelable/easy strip versions available

Connector Options

- OPTITAP® to OPTITAP®
 - OPTITAP® to SC/APC
 - OPTITAP® to LC
 - OPTITAP® pigtail
- * custom breakouts : Length OD style (armored and non-armored)

Performance Specifications

Fiber Type	Fiber Interface	Insertion Loss (dB)		Return Loss (dB)
		Typ	Max	
Single Mode	LC/SC - UPC	0.20	0.25	-57
	LC/SC - APC	0.20	0.25	-65
	OptiTap®	0.15	0.35	-65

Features and Benefits

- Durable UV resistant construction
- Available with toneable and dielectric cable designs
- Cost effective solution for in house termination
- Low insertion loss
- IP68 rated for water and dust ingress protection
- Available with one or both ends connectorized
- Flat Drop is self-supporting at 40 lbs of installation tension, 150ft
- Designed for aerial, direct buried or duct installation
- Mechanical performance: IEC 61754-4 standard
- RoHS and REACH materials compliant

Ordering Information

HE	# of Fibers	SM	Fiber Type	Conn		Conn		BO		Breakout Type		Length
	1		D1 SST - drop dielectric	57	OPTITAP®	57	OPTITAP®	T	12"	3	3MM indoor	
			D3 SST - drop toneable	SA	SC/ACP	SA	SC/APC	P	8"	32	3MM outdoor	
			D6 tight buffered dielectric	SC	SC/UPC	SC	SC/UPC					
			D7 tight buffered toneable	LC	LC/UPC	LC	LC/UPC					
			AD armor	LA	LC/APC	LA	LC/APC					
			IO round indoor/outdoor									

Consult Sales for custom breakouts

Part Number Example

Part#	Product Description	Units / Delivery
HE01SMD15757-100F	1 fiber, single tube, OptiTap® to OptiTap® flat drop, singlemode - 100ft	1



260 Progress Drive
Manchester, CT 06042

P: 800-557-8818
F: 860-649-6002
info@netsource-inc.com

Our Commitment to Quality and Customer Service is Our Connection to You