


# NID Enclosures




- 2x SC ports
  - 1x2 Splitter or 4 Splices
  - Input: OptiTap® compatible connector
  - Output: Flat Drop, ROC, and 3-16.2mm Round Cable
  - Hinged lid opens to 60°, locks securely, and is fully removable
  - Screw lock
  - Dimensions: 8.91" x 6.00" x 1.80"
- PN: HE-02NID-05



- 2x SC ports
  - 1x2 Splitters or 4 Splices
  - Input/Output: Liquid tight grommets for Flat Drop, ROC, and 3-5mm Round Cable
  - Hinged lid opens to 60°, locks securely, and is fully removable
  - Screw lock
  - Dimensions: 8.91" x 6.00" x 1.80"
- PN: HE-02NID-05LT



- 4x SC ports
  - 1x2 or 1x4 Splitters
  - Input/Output: Flat Drop, ROC, and 3-16.2mm Round Cable
  - Hinged lid opens to 60°, locks securely, and is fully removable
  - 1" Conduit tie down
  - Screw lock
  - Dimensions: 7.00" x 7.00" x 2.275"
- PN: HE-04NID-02



- 2x SC ports
  - 1x2 Splitter
  - Input: 1x10mm and dielectric Flat Drop
  - Output: 4.8mm
  - Wall mount
  - Key lock
  - Dimensions: 8.18" x 6.02" x 2.04"
- PN: HE-02NID-02



- Accepts Ubiquiti ONU
  - Input/Output: Flat Drop, ROC, and 3-16.2mm Round Cable
  - Built in storage 50ft of cable
  - 1" Conduit tie down
  - Screw lock
  - Dimensions: 9.89" x 10.28" x 2.95"
- PN: SP-NID01-ONU



- 1x SC port
  - Input/Output: Flat Drop, ROC, and 3-16.2mm Round Cable
  - Built in storage 50ft of cable
  - 1" Conduit tie down
  - Screw lock
  - Dimensions: 9.89" x 10.28" x 2.95"
- PN: SP-NID01-SPL



- Accepts 1 LGX Adapter Panel (up to 24 fibers and 24 Splices)
  - Input/Output: Flat Drop, ROC, and 3-16.2mm Round Cable
  - 1" Conduit tie down
  - Built in storage 50ft of cable
  - Screw lock
  - Dimensions: 9.89" x 10.28" x 2.95
- PN: SP-NID01-LGX



- 12 SC or 24 LC
  - 1x8 Splitter or 12 Splices
  - Input: Liquid tight grommet Flat Drop, or 1x10mm cable
  - Output: Liquid tight grommet 2x9-18mm Round Cable
  - Key lock
  - Dimensions: 10.15" x 7.32" x 2.48"
- PN: HE-12NID-01



To view more of our broadband products, scan the QR code