

Pullable Fiber Drop Cable Assemblies



Product Overview:

NetSource's Pullable Fiber Drop Cable Assemblies provide a clean, protected solution for FTTH and FTTP installations. Each assembly features a factory-terminated SC/APC ferrule with a threaded pull cap that shields the connector as it's pulled through walls, conduits, or microducts. Once installed, the pull cap is removed and the housing snaps into place—eliminating the need for splicing or field termination. Built with bend-insensitive single-mode fiber (G.657.A2 or G.657.B3), the 3.0mm cable easily navigates tight routing paths and is available in black or white jackets for indoor or outdoor use.

Insertion Loss:

Insertion Loss (Typical)	<0.3 dB/km
Return Loss	≥0.5 dB/km

Features & Benefits:

- Tool-less installation (3/8" hole to insert cable)
- SC/APC ferrule with threaded pull cap (Housing snaps on after pulling through wall)
- Reduces installation time
- Eliminates in-field splicing
- Available in armored and non-armored cables
- Built-in pulling eye
- Jacket color is available in black or white

Environmental & Mechanical Properties:

- Operating Temperature: -20°C to 70°C (-4°F to 158°F)
- Minimum Bend Radius: 5mm (G.657.A2), 7mm (G.657.B3)
- Compliance: RoHS, REACH, GR-20, GR-326, Telcordia, BABA Compliant