


# OST-8 OptiTap®-Compatible Splice Terminal

## OVERVIEW

The OST-8 OptiTap®-compatible splice terminal is a hardened OSP fiber splice terminal designed for fiber distribution and subscriber drop connectivity in FTTH access networks. It provides a centralized splice and distribution point between feeder and subscriber drop cables.

## GENERAL SPECIFICATIONS

- **Hardened Drop Ports:** 8 OptiTap®-compatible ports
- **Optical Splitter:** 4 PLC splitters
- **Splice Capacity:** 96 fibers
- **Fiber Management:** Integrated fiber routing, splice organization, and fiber storage
- **Feeder Cable:** 17.5 mm maximum OD × 2
- **Mounting:** Strand, pole, pedestal, or ground vault
- **Housing Material:** UV-resistant, high-impact thermoplastic
- **Sealing Method:** Mechanical gasket with compression-based closure system
- **Dimensions:** 365 × 195 × 133 mm



## CONFORMANCE

- **RoHS/REACH:** Environmental Compliance

## ENVIRONMENTAL & MECHANICAL PROPERTIES

- **Ingress Protection:** IP68
- **Operating Temperature:** -40°C to +65°C (-40°F to +149°F)
- **Storage Temperature:** -20°C to +65°C (-4°F to 149°F)

Rev 00 | 09/28/2026