

Flat Drop Cable Assemblies

MADE IN THE USA



OVERVIEW

Self-Supporting Flat Drop Cable Assemblies are designed for fiber distribution and subscriber connectivity in FTTH and FTTx networks. They provide a connection from distribution terminals to subscriber locations and support aerial, direct-buried, and conduit installations. Available in toneable and dielectric configurations, assemblies may be supplied stubbed for splicing or pre-terminated on one or both ends for direct connection.

GENERAL SPECIFICATIONS

- Fiber Count: 1 Fiber
- Fiber Type: Singlemode OS2
- Fiber Compliance: ITU-T G.652.D
- Cable Construction: Corning SST-Drop™ — Dielectric or Toneable
- Connector Types: OptiTap®, SC, LC (UPC/APC)
- Breakout Jacket: 900 µm, 2 mm, 3 mm, or Ruggedized
- Termination: Stubbed or pre-terminated on one or both ends
- Dielectric Cable Dimensions: 8.1 × 4.5 mm
- Toneable Cable Dimensions: 10.2 × 4.7 mm

OPTICAL PERFORMANCE

- Insertion Loss SM: ≤ 0.15 dB
- Return Loss APC: ≥ 65 dB
- Return Loss UPC: ≥ 55 dB



BABA-Compliant configurations available.

Contact NetSource for applicable part numbers and compliance documentation.

Rev. 00 | 10/20/2026

Flat Drop Cable Assemblies

CONFORMANCE

- Telcordia GR-20 — Cable: Outside Plant Fiber Optic Cable Requirements
- Telcordia GR-3120 — Connector: Hardened Fiber Optic Connector Requirements
- RDUP (RUS) — Cable: USDA Rural Development Programs
- RoHS/REACH

ENVIRONMENTAL & MECHANICAL PROPERTIES

- Ingress Protection: IP68 — OptiTap® Interface
- Operating Temperature: -40°C to +70°C (-40°F to +158°F)
- Storage Temperature: -40°C to +70°C (-40°F to +158°F)
- Installation Temperature: -30°C to +70°C (-22°F to +158°F)
- Jacket Material: Polyethylene (PE), UV-resistant for outdoor applications
- Minimum Bend Radius: 80 mm (3.15 in)
- Maximum Tensile Load — Short Term: 1,350 N (303 lbf)
- Maximum Tensile Load — Long Term: 400 N (90 lbf)
- OptiTap® Connector Pulling Tension: 100 lb

PART NUMBERS

HE	# of Fibers	Cable Type	Cable Construction	Connector 1	Connector 2	Breakout Length	Breakout Jacket	Length
HE	01	SM: Singlemode OS2	D1: Dielectric D3: Toneable	57: OptiTap® SC: SC/UPC SA: SC/APC	57: OptiTap® SC: SC/UPC SA: SC/APC	T: 12"	2: 2 mm 3: 3 mm	XXXFT XXXM

Example: HE01SMD357SAT2-250FT

1-Fiber OS2 / Toneable / OptiTap® to SC/APC / 12" breakout / 2 mm jacket / 250 ft

Rev. 00 | 10/20/2026

Flat Drop Cable Assemblies

SAMPLE CONFIGURATIONS

SC/APC to SC/APC



SC/APC to Blunt End



OptiTap® to SC/APC



OptiTap® to Blunt End



OptiTap® to OptiTap®



Rev. 00 | 10/20/2026