

OptiTap® Multiport Terminals - Stubbed

OVERVIEW

NetSource Stubbed OptiTap® Compatible Multiport Terminals (MST) provide a rugged, environmentally sealed connection point for connecting subscriber drop cables to the fiber network. Factory-terminated hardened ports provide quick, plug-and-play connections for FTTH and FTTx deployments.

GENERAL SPECIFICATIONS

- Port Count: 2, 4, 6, 8, and 12 Ports
- Fiber Type: Singlemode OS2
- Cable Construction: Self-Supporting Flat Drop — Dielectric or Toneable
- Subscriber Interface: OptiTap® Compatible
- Cable Tail Lengths: 25 ft to 2,500 ft
- Mounting: Pole, Aerial, or Wall; Brackets Included
- Pedestal Compatibility: Most 8–10 in. Pedestals

DIMENSIONS

Port Configuration	Dimensions (H x L x W)
2 / 4 Port	3.65 × 8.26 × 4.38 in.
6 Port	3.65 × 11.25 × 4.38 in.
8 Port	3.65 × 11.09 × 4.38 in.
12 Port	4.25 × 14.25 × 5.32 in.



4-Port



6-Port



8-Port



12-Port

Rev. 00 | 10/2/2026

OptiTap® Multiport Terminals - Stubbed

OPTICAL PERFORMANCE

- Insertion Loss — Typical: ≤ 0.15 dB
- Return Loss — APC / OptiTap®: ≤ -65 dB

CONFORMANCE

- Telcordia GR-771 — Terminal: Tested to applicable environmental and mechanical requirements
- Telcordia GR-3120 — Connector: Hardened Fiber Optic Connector Requirements
- Telcordia GR-20 — Cable: Outside Plant Fiber Optic Cable Requirements
- RoHS/REACH

ENVIRONMENTAL & MECHANICAL PROPERTIES

- Ingress Protection: IP68 — OptiTap® Interface
- Operating Temperature: -40°C to $+70^{\circ}\text{C}$ (-40°F to $+158^{\circ}\text{F}$)
- Cold Mate/Demate Performance: Tested to -40°C (-40°F)

PART NUMBERS

HE	-	Port Count	P	Cable Type	Cable Construction	Connector	-	Length
		2 4 6 8 12		SM: Singlemode OS2	D1: Dielectric D3: Toneable	57: Hardened SC/ APC		XXXFT

Example: HE-04PSMD357-150FT

4-Port / Singlemode OS2 / Toneable / OptiTap® to SC/APC / 150 ft



BABA-Compliant configurations available.

Contact NetSource for applicable part numbers and compliance documentation.

Rev. 00 | 10/2/2026