BUILD AMERICA BUY AMERICA COMPLIANT

BABA NETSOURCE Copper and Fiber Systems Solutions

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
00	INITIAL RELEASE	04-08-26	BDLS



Parameter	1x2	1x3	1x4	1x6	1x8	1x12	1x16	1x24	1x32	1x48	1x64	1x128
Working Wavelength (nm)	1260-1650											
Fiber Type	G657A1 or Customized											
Insertion Loss (dB)	3.9	6.1	7.2	9	10.2	12.5	13.5	15.5	16.8	18.4	20.1	23.8
Uniformity (dB)	≤0.4	≤0.5	≤0.5	≤0.6	≤0.8	≤1.0	≤1.0	≤1.5	≤1.5	≤1.8	≤1.8	≤2.5
Polarization Dependent Loss (dB)	≤0.25	≤0.25	≤0.25	≤0.25	≤0.25	≤0.3	≤0.3	≤0.3	≤0.3	≤0.4	≤0.35	≤0.35
Return Loss (dB)	≥55											
Directionality (dB)	≥55											
Fiber Length (m)	1.0 or Customized											
Temperature Stability (dB)	-40°C to -85°C (≤0.5)											
Working Temperature °C	-40°C to -85°C											
Storage Temperature °C	-40°C to -85°C											
Maximum Power (nW)	1,000											

NOTICE
THIS DRAWING CONTAINS CONFIDENTIAL AND/OR PROPRIETARY INFORMATION INTENDED FOR THE USE ONLY BY THE INDIVIDUAL(S) SPECIFIED HERE AND ONLY FOR THE PURPOSE(S) PROVIDED AND MUST NOT BE DISCLOSED, COPIED, OR LOANED, IN WHOLE OR IN PART OR USED FOR ANY PURPOSE WITHOUT PRIOR WRITTEN CONSENT FROM NETSOURCE INC.

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MM.

NetSource, Inc.
260 Progress Drive
Manchester, CT 06042
Tel (860) 649-6000
www.netsource-inc.com

TITLE:

DRAWN BY: TA	DATE: 04-08-26	SIZE: CUSTOM	PART NUMBER: BA-1X8SM53-2000	REV:
INITIATED BY: BDLS	DATE: 04-08-26	SCALE: CUSTOM		SHEET: 1 OF 1